



# Chamfering & Deburring Unit



SPMN 1203

## VCF-500

Accessory: Side Mill Cutter Insert SPUN 422



ORDER NO.	CODE NO.
VCF-500	1023-001
VCF-500W	1023-002
VCF-500F	1023-003

### PRACTICAL

- A. UNIVERSAL APPLICATION.
- B. SIMPLIFIED OPERATION.
- C. FAST-ACCURATE-RATIONAL.
- D. TIME SAVED.

- Tool cabinet stand VTC-20, 440 x 340 x 800 mm  
CODE NO. 3405-221  
PAGE A84



## VCF-500W

Accessory: Grinding Wheel  
100Øx50x17Ø



### FEATURES FOR VCF-500, 500W, 500F

1. Simplified operation, suitable for unskilled personnel.
2. Easily to be bevelled for any length made of steel, cast iron, nonferrous metals, plastics, acrylic etc.
3. 500 : With exchangeable carbide inserts, insert can be changed easily to save cost and increase working ability.
4. 500W: With flange for grinding wheel, suit for steel material, heat treatment workpiece, can be bevelled or chamfered.
5. 500F : Working base on surface milling principles, the deburring processing surface is same as the milling machine surface.

- ※ Please confirm voltage & phase when order.
- ※ Guaranteed for 3 months



## VCF-500F

Accessory: Face Milling Cutter Insert SEKN 1203



### TECHNICAL DATA

	500	500W	500F
Space requirement	500x320mm	500x440mm	500x220mm
Weight(kgs)	28.5	29.1	29
Voltage	3Ø 220V or 1Ø 110V/220V 50HZ/60HZ 3Ø 380V/415V		
Motor output	0.7KW		
Speed	3500 r.p.m.		
Length of guide rails	500mm	500mm	500mm
Height of bevel	0-3mm		
Bevel angle	15°~45° (Changable)	45°	45°

PLEASE NOTIFY VOLTAGE & PHASE, WHEN YOU ORDERING.  
C.E MARK REQUESTED