Chamfering & Deburring Unit WERTEX®






VCF-500S Accessory: Sanding Disc 165Øx22Ø

| | Light duty |
|--|------------|
| VCF-600 Insert SPMW 321 ZSPMW 090308 | |



Heavy duty



| ORDER NO. | RDER NO. CODE NO. | |
|-----------|-------------------|--|
| VCF-500S | 1023-004 | |
| VCF-600 | 1023-005 | |
| VCF-700 | 1023-006 | |

PRACTICAL

- A. USING SAND-CLOTH ROLLER FOR CUTTING.
- B. GOOD FOR STEEL. CAST IRON HARDEN PARTS.
- C. NOT FOR SOFT IRON OR ALUMINUM.
- D. IF USED BENT WORKPIECE, THE CHAMFERING SURFACE WOULD NOT SMOOTHLY STRAIGHT.

FEATURES FOR VCF-

- 1. 500S: Uses sanding disc, can debur soft and rigid materials.
- 2. 600 : Easy to carry and time-saving. suitable for large size workpiece which can't be easily moved. The tools can be chamfered 0-3mm bevel angle, radius, arc angle, irregular shape. straight line, outer curve and etc.
- 3.700 : The machine is used to carry out chamfering operations on any kind of ferrous material in particular steel and cast iron. Equipped with square-shaped tungsten carbide inserts-12.7x12.7x3.18 ISO 1203 SPUN. Simplified operation suitable for unskilled personnel. 3Ø220V/3Ø380V
- ※Please confirm voltage & phase when order.

TECHNICAL DATA

| Space requirement | VCF-500S | VCF-600 | VCF-700 | | |
|-----------------------|---------------------------------|--------------|-----------------------|--|--|
| | 330x410 | 380x130 | 360x200x260 | | |
| Weight(kgs) | 26 | 3.7 | 14 | | |
| Voltage | 3Ø220V or 1Ø110V/220V 50HZ/60HZ | | | | |
| Motor output | 0.7KW | 0.62KW | 0.37KW | | |
| Speed | 3500 r.p.m. | 12000 r.p.m. | 3500 r.p.m. | | |
| Lenght of guide rails | 320mm | 100mm | 200mm | | |
| Height of bevel | 0-3mm | 0-3mm | 0-7mm | | |
| Bevel angle | 45° | 45° | 15°~45° Adjustable | | |

PLEASE NOTIFY VOLTAGE & PHASE, WHEN YOU ORDERING.